



“Torsiometer” torque screwdriver, maximum torque: 600 cNm



Order data

Order number	659200 600
GTIN	4018754118939
Item class	63A

Description

Version:

Ergonomic handle with torsion rod measuring device.
Scale with memory pointer for right hand threads.

Units of measurement: cN·m, lbf·in

Application:

For controlled single tightening of screws and for controlled measurements.

Standard:

Geprüft nach DIN EN ISO 6789.

Note:

The guaranteed measuring accuracy of the torque is achieved only once the torque range has been calibrated to DIN EN ISO 6789.

Direction of tightening: For right- and left-hand tightening

Torque measuring accuracy: $\pm 4\%$

Bit socket: F 6.3

Calibration: O3

Torque measuring accuracy: $\pm 4\%$

Overall length L: 185 mm

Torque range: 120 - 600 cNm

Torque range: 12 - 52 lbf·in

Scale graduation, 1 graduation =: 20 cNm

Technical description

maximum torque	600 cNm
Scale graduation, 1 graduation =	20 cNm

Display	analogue
Torque measuring accuracy	±4 %
Bit socket	F 6.3
Torque range	120 - 600 cNm
Torque range	12 - 52 lbf·in
Weight	230 g
Setting the trigger value	Memory pointer
Adjustable trigger value	non-adjustable
Overall length L	185 mm
Measurement process	Torque
Trigger principle	mechanical short-travel release
Standard	DIN EN ISO 6789
Feedback	displaying
Connection format	Bit holder 1/4 inch
Reversible reading	cNm
Reversible reading	lbf·in
Series	TORSIOMETER 760
Calibration	O3
Direction of tightening	For right- and left-hand tightening
Data can be recorded	no
Measurement technology	mechanical
Release signalling	akustisk
Release signalling	haptisk
Torque fixed setting	no
Type of product	Torque screwdriver

Services

Calibration Torque wrench both ends maximum torque
1000/2 Nm

018821 1000/2

018940

Labelling laser-etched Type
