

## Garant

**Torque screwdriver with scale, to take interchangeable blades, maximum torque: 200 cNm**



### Order data

Order number	659906 200
GTIN	4045197611222
Item class	61E

### Description

#### Version:

**Power grip** with comfortable easy-grip **Haptoprene®** surface allows transmission of the required torque with no problems even with **wet or oily hands**. On reaching the set torque value, the screwdriver can be felt and heard to trigger and is then again immediately ready for use. The release torque is higher than the tightening torque (overload protection). The desired torque is set using an adjustment wheel at the end of the handle. Putting the wheel into the locked position prevents inadvertent changes to the setting. Easy to read micrometer scale, protected against dirt. To **take 6 mm interchangeable blades** (No. 659920 – 659928).

#### Standard:

Geprüft nach DIN EN ISO 6789.

#### Note:

The guaranteed measuring accuracy of the torque is achieved only once the torque range has been calibrated to DIN EN ISO 6789.

Direction of tightening: Right-hand tightening

Torque measuring accuracy:  $\pm 6\%$

Test certificate: Manufacturer's test certificate

Calibration: O1

Torque measuring accuracy:  $\pm 6\%$

Overall length L: 124 mm

Torque range: 40 - 200 cNm

Torque range: 0.4 - 2 Nm

Scale graduation, 1 graduation =: 5 cNm

maximum  $\varnothing$ : 35 mm

### Technical description

suitable interchangeable blades	6 mm
Scale graduation, 1 graduation =	5 cNm
Display	analogue
maximum torque	200 cNm
Torque measuring accuracy	±6 %
Torque range	40 - 200 cNm
Torque range	0.4 - 2 Nm
Connection format	exchangeable blade
Overall length L	124 mm
Feedback	triggering
Standard	DIN EN ISO 6789
Reversible reading	Nm
Setting the trigger value	with adjustment scale
Weight	97 g
Trigger principle	mechanical slip clutch
Measurement process	Torque
Adjustable trigger value	adjustable
Calibration	O1
Direction of tightening	Right-hand tightening
Test certificate	Manufacturer's test certificate
Data can be recorded	no
Measurement technology	mechanical
Release signalling	akustisk
Release signalling	haptisk
maximum Ø	35 mm
Torque fixed setting	no
Type of product	Torque screwdriver

## Services

Calibration Torque wrench maximum torque 400 Nm

018820 400

---

## Accessories

Electronic torque screwdriver tester "TST" maximum torque 2 Nm

654300 2

Torque test and calibration device maximum torque 2 Nm

654395 2