

**Garant**

**Torque screwdriver without scale, to take D 6.3 bits, maximum torque: 200 cNm**



## Order data

Order number	659907 200
GTIN	4045197923493
Item class	61E

## Description

### Version:

**Power grip** with comfortable easy-grip **Haptoprene®** surface allows transmission of the required torque with no problems even with **wet or oily hands**. On reaching the set torque value, the screwdriver can be felt and heard to trigger and is then again immediately ready for use. The release torque is higher than the tightening torque (overload protection).

**Bit holder with magnet** to take C 6.3 bits.

The desired torque can be set by stepless adjustment using a torque analyser (No. 654300 – 654460) and a 5 AF hexagon screwdriver (not supplied). When 20 or more of a size are ordered, they can be factory pre-set.

### Standard:

Geprüft nach DIN EN ISO 6789.

### Note:

The guaranteed measuring accuracy of the torque is achieved only once the torque range has been calibrated to DIN EN ISO 6789.

Direction of tightening: Right-hand tightening

Torque measuring accuracy:  $\pm 6\%$

Bit socket: D 6,3

Test certificate: Manufacturer's test certificate

Calibration: O6

Calibration: O7

Torque measuring accuracy:  $\pm 6\%$

Overall length L: 144 mm

set torque: 1.2 Nm

Torque range: 40 - 200 cNm

Torque range: 0.4 - 2 Nm

maximum  $\varnothing$ : 35 mm

## Technical description

maximum torque	200 cNm
Torque measuring accuracy	±6 %
set torque	1.2 Nm
Bit socket	D 6,3
Torque range	40 - 200 cNm
Torque range	0.4 - 2 Nm
Connection format	Bit holder 1/4 inch
Reversible reading	Nm
Overall length L	144 mm
Setting the trigger value	without adjustment scale (requires a testing device)
Trigger principle	mechanical slip clutch
Feedback	triggering
Standard	DIN EN ISO 6789
Weight	112 g
Adjustable trigger value	pre-set
Measurement process	Torque
Calibration	O6
Calibration	O7
Direction of tightening	Right-hand tightening
Test certificate	Manufacturer's test certificate
Data can be recorded	no
Measurement technology	mechanical
Release signalling	akustisk
Release signalling	haptisk
maximum Ø	35 mm
Type of product	Torque screwdriver

## Services

Adjustment Torque wrench without scale	018890
Labelling laser-etched Type	018940
Calibration and adjustment Torque wrench without scale maximum torque 400 Nm	018891 400
Calibration Torque wrench maximum torque 400 Nm	018820 400

---

## Accessories

Electronic torque screwdriver tester "TST" maximum torque 2 Nm	654300 2
Hexagon key L-wrench with retainer ball, chrome-plated Hexagon 5 mm	626085 5
Torque test and calibration device maximum torque 2 Nm	654395 2