



## Torque screwdriver with digital display, to take interchangeable blades, maximum torque: 200 cNm



### Order data

Order number	659912 200
GTIN	7610733276233
Item class	63D

### Description

#### Version:

**Power grip** with non-allergenic elastomer coating allows transmission of the required torque with no problems even with **wet or oily hands**. On reaching the set torque value, the screwdriver can be felt and heard to trigger and is then again immediately ready for use. The release torque is higher than the tightening torque (overload protection).

Torque adjustment **without using tools** just pull the cap and turn it. The torque setting is displayed in a window (**digital display at the end of the handle**). Built-in electronics with NFC interface. Battery can be replaced by the customer (button cell CR 1/3 N; 3V). **Units of measure:** N·m, lbf·ft. To **take 6 mm interchangeable blades** (No. 659920 – 659928).

#### Application:

For controlled tightening of screws to a pre-set torque.

#### Standard:

Geprüft nach DIN EN ISO 6789.

#### Note:

The guaranteed measuring accuracy of the torque is achieved only once the torque range has been calibrated to DIN EN ISO 6789.

Direction of tightening: Right-hand tightening

Torque measuring accuracy:  $\pm 6\%$

Test certificate: Manufacturer's test certificate

Calibration: O1

Torque measuring accuracy:  $\pm 6\%$

Overall length L: 126 mm

Torque range: 40 - 200 cNm

Torque range: 0.4 - 2 Nm

Resolution: 2 cNm

suitable interchangeable blades: 6 mm

## Technical description

Torque range	0.4 - 2 Nm
Torque range	40 - 200 cNm
maximum torque	200 cNm
Display	digital
suitable interchangeable blades	6 mm
Torque measuring accuracy	±6 %
Resolution	2 cNm
Reversible reading	cNm
Reversible reading	lbf·in
Standard	DIN EN ISO 6789
Adjustable trigger value	adjustable
Weight	97 g
Connection format	exchangeable blade
Setting the trigger value	digital, adjustable
Overall length L	126 mm
Feedback	triggering
Trigger principle	mechanical slip clutch
Measurement process	Torque
Calibration	O1
Direction of tightening	Right-hand tightening
Test certificate	Manufacturer's test certificate
Data can be recorded	no
Measurement technology	mechanical
Release signalling	akustisk
Release signalling	haptisk
Type of product	Torque screwdriver

## Services

Calibration Torque wrench maximum torque 400 Nm

018820 400