

Torque screwdrivers with digital display, to take D 6.3 bits, maximum torque: 50 cNm



Order data

Order number	659913 50
GTIN	7610733276318
Item class	63D

Description

Version:

Power grip with non-allergenic elastomer coating allows transmission of the required torque with no problems even with **wet or oily hands.** On reaching the set torque value, the screwdriver can be felt and heard to trigger and is then again immediately ready for use. The release torque is higher than the tightening torque (overload protection).

Torque adjustment **without using tools** just pull the cap and turn it. The torque setting is displayed in a window (**digital display at the end of the handle**). Built-in electronics with NFC interface. Battery can be replaced by the customer (button cell CR 1/3 N; 3V). **Units of measure:** N·m, lbf·ft.

Bit holder with magnet to take C 6.3 bits.

Application:

For controlled tightening of screws to a pre-set torque.

Standard:

Geprüft nach DIN EN ISO 6789.

Note:

The guaranteed measuring accuracy of the torque is achieved only once the torque range has been calibrated to DIN EN ISO 6789.

Direction of tightening: Right-hand tightening

Torque measuring accuracy: ±6 %

Bit socket: D 6,3

Test certificate: Manufacturer's test certificate

Calibration: 01

Torque measuring accuracy: ±6 %

Overall length L: 127.5 mm Torque range: 10 - 50 cNm Torque range: 0.1 - 0.5 Nm

Resolution: 1 cNm

Technical description

maximum torque	50 cNm
Resolution	1 cNm
Bit socket	D 6,3
Torque range	0.1 - 0.5 Nm
Torque measuring accuracy	±6 %
Torque range	10 - 50 cNm
Display	digital
Feedback	triggering
Measurement process	Torque
Trigger principle	mechanical short-travel release
Adjustable trigger value	adjustable
Standard	DIN EN ISO 6789
Setting the trigger value	digital, adjustable
Connection format	Bit holder 1/4 inch
Overall length L	127.5 mm
Reversible reading	Nm
Reversible reading	lbfft
Calibration	01
Direction of tightening	Right-hand tightening
Test certificate	Manufacturer's test certificate
Data can be recorded	no
Measurement technology	mechanical
Release signalling	acoustic
Release signalling	acoustic
Torque fixed setting	no
Type of product	Torque screwdriver



Services

DAkkS calibration Torque wrench maximum torque 1000 Nm	018830 1000
Calibration Torque wrench maximum torque 400 Nm	018820 400