



Torque screwdriver with scale, maximum torque: 300 cNm



Order data

Order number	659933 300
GTIN	4013288192158
Item class	63F

Description

Version:

Kraftform handle for easy transmission of the required torque. With **Rapidaptor** quick-change holder for 1/4 inch bits with C 6.3 **and** E 6.3 shank.

Torque setting by hand using a micrometer scale (from size 600 using the integral auxiliary tool or a 17AF open spanner).

Function:

When the set torque is reached the screwdriver triggers, with clearly audible and perceptible signals. The triggering torque is unrestricted.

Standard:

Geprüft nach DIN EN ISO 6789.

Note:

The guaranteed measuring accuracy of the torque is achieved only once the torque range has been calibrated to DIN EN ISO 6789.

Rapidaptor free-running coupling shank available from our eShop (No. 675035 size 6.3F).

Direction of tightening: Right-hand tightening

Torque measuring accuracy: $\pm 6\%$

Bit socket: D 6,3

Bit socket: F 6.3

Test certificate: Manufacturer's test certificate

Calibration: O1

Torque measuring accuracy: $\pm 6\%$

Overall length L: 155 mm

Torque range: 120 - 300 cNm

Torque range: 1.2 - 3 Nm

Scale graduation, 1 graduation =: 10 cNm

Technical description

maximum torque	300 cNm
Display	analogue
Scale graduation, 1 graduation =	10 cNm
Torque measuring accuracy	±6 %
Bit socket	D 6,3
Bit socket	F 6.3
Torque range	120 - 300 cNm
Torque range	1.2 - 3 Nm
Connection format	Bit holder 1/4 inch
Overall length L	155 mm
Standard	DIN EN ISO 6789
Feedback	triggering
Trigger principle	mechanical short-travel release
Adjustable trigger value	adjustable
Reversible reading	cNm
Setting the trigger value	with adjustment scale
Measurement process	Torque
Calibration	O1
Direction of tightening	Right-hand tightening
Test certificate	Manufacturer's test certificate
Data can be recorded	no
Measurement technology	mechanical
Release signalling	akustisk
Release signalling	haptisk
Type of product	Torque screwdriver

Services

Calibration Torque wrench maximum torque 400 Nm	018820 400
---	------------

