



Torque screwdriver without scale, maximum torque: 300 cNm



Order data

Order number	659934 300
GTIN	4013288102928
Item class	63F

Description

Version:

Kraftform handle for easy transmission of the required torque. With **Rapidaptor** quick-change holder for 1/4 inch bits with C 6.3 **and** E 6.3 shank.

The torque can be set using a torque analyser (No. 654300 – 654460) and a 7AF hexagon screwdriver (10AF for size 600). **The torque screwdrivers are factory-set to the most frequently used torque setting.**

Function:

When the set torque is reached the screwdriver triggers, with clearly audible and perceptible signals. The triggering torque is unrestricted.

Standard:

Geprüft nach DIN EN ISO 6789.

Note:

The guaranteed measuring accuracy of the torque is achieved only once the torque range has been calibrated to DIN EN ISO 6789.

Rapidaptor free-running coupling shank available from our eShop (No. 675035 size 6.3F).

Direction of tightening: Right-hand tightening

Torque measuring accuracy: $\pm 6\%$

Bit socket: D 6,3

Bit socket: F 6.3

Test certificate: Manufacturer's test certificate

Calibration: O6

Torque measuring accuracy: $\pm 6\%$

Overall length L: 155 mm

set torque: 1.2 Nm

Torque range: 120 - 300 cNm

Torque range: 1.2 - 3 Nm

1 turn (360°) corresponds to: 20 cNm

Technical description

set torque	1.2 Nm
1 turn (360°) corresponds to	20 cNm
maximum torque	300 cNm
Torque measuring accuracy	±6 %
Bit socket	D 6,3
Bit socket	F 6.3
Torque range	120 - 300 cNm
Torque range	1.2 - 3 Nm
Feedback	triggering
Standard	DIN EN ISO 6789
Overall length L	155 mm
Connection format	Bit holder 1/4 inch
Reversible reading	cNm
Adjustable trigger value	pre-set
Setting the trigger value	uden indstillingskala (kræver testapparat)
Trigger principle	mechanical short-travel release
Measurement process	Torque
Calibration	O6
Direction of tightening	Right-hand tightening
Test certificate	Manufacturer's test certificate
Data can be recorded	no
Release signalling	akustisk
Release signalling	haptisk
Measurement technology	mechanical
Type of product	Torque screwdriver

Services

Adjustment Torque wrench without scale	018890
Calibration and adjustment Torque wrench without scale maximum torque 400 Nm	018891 400

Accessories

Electronic torque screwdriver analyser maximum torque 11 Nm	654390 11
Electronic torque screwdriver tester "TST" maximum torque 10 Nm	654300 10
Torque test and calibration device maximum torque 5 Nm	654395 5