



Torque screwdriver without scale, maximum torque: 600 cNm



Order data

Order number	659934 600
GTIN	4013288102935
Item class	63F

Description

Version:

Kraftform handle for easy transmission of the required torque. With **Rapidaptor** quick-change holder for 1/4 inch bits with C 6.3 **and** E 6.3 shank.

The torque can be set using a torque analyser (No. 654300 – 654460) and a 7AF hexagon screwdriver (10AF for size 600) . **The torque screwdrivers are factory-set to the most frequently used torque setting.** With pistol grip for delivering high torques.

Function:

When the set torque is reached the screwdriver triggers, with clearly audible and perceptible signals. The triggering torque is unrestricted.

Standard:

Geprüft nach DIN EN ISO 6789.

Note:

The guaranteed measuring accuracy of the torque is achieved only once the torque range has been calibrated to DIN EN ISO 6789.

Rapidaptor free-running coupling shank available from our eShop (No. 675035 size 6.3F).

Direction of tightening: Right-hand tightening

Torque measuring accuracy: $\pm 6\%$

Bit socket: F 6.3

Bit socket: D 6,3

Test certificate: Manufacturer's test certificate

Calibration: O6

Torque measuring accuracy: $\pm 6\%$

Overall length L: 150 mm

set torque: 3 Nm
 Torque range: 300 - 600 cNm
 Torque range: 3 - 6 Nm
 1 turn (360°) corresponds to: 50 cNm

Technical description

set torque	3 Nm
maximum torque	600 cNm
1 turn (360°) corresponds to	50 cNm
Torque measuring accuracy	±6 %
Bit socket	F 6.3
Bit socket	D 6,3
Torque range	300 - 600 cNm
Torque range	3 - 6 Nm
Feedback	triggering
Adjustable trigger value	pre-set
Trigger principle	mechanical short-travel release
Overall length L	150 mm
Standard	DIN EN ISO 6789
Setting the trigger value	uden indstillingskala (kræver testapparat)
Connection format	Bit holder 1/4 inch
Reversible reading	cNm
Measurement process	Torque
Calibration	O6
Direction of tightening	Right-hand tightening
Test certificate	Manufacturer's test certificate
Data can be recorded	no
Measurement technology	mechanical
Release signalling	akustisk
Release signalling	haptisk

Type of product	Torque screwdriver
-----------------	--------------------

Services

Adjustment Torque wrench without scale	018890
--	--------

Calibration and adjustment Torque wrench without scale maximum torque 400 Nm	018891 400
---	------------

Accessories

Electronic torque screwdriver tester "TST" maximum torque 10 Nm	654300 10
--	-----------

Torque test and calibration device maximum torque 10 Nm	654395 10
--	-----------

Electronic torque screwdriver analyser maximum torque 11 Nm	654390 11
--	-----------