



Torque screwdriver with digital display, maximum torque: 300 cNm



Order data

Order number	659935 300
GTIN	4010995368876
Item class	63K

Description

Version:

High-quality comfortable metal-plastic composite handle ensures ergonomic working and easy application of the set torques. Quick and easy reading and setting **via the large digital display**. Automatic switch-off after 15 seconds (battery life at least 1 year). The battery can be changed at the factory or during recalibration. Display changeover between Nm and lbf·in. Includes bit-holder blade No. 659932 to take 1/4 inch bits.

Units of measure: N·m, lbf·in

Advantage:

An **integral counter function** records the number of tightening operations, providing the basis for monitoring by test instruments.

Function:

On reaching the set torque value, the screwdriver can be felt and heard to trigger and is then again immediately ready for use.

Application:

For controlled tightening of screws to a pre-set torque.

Standard:

Geprüft nach DIN EN ISO 6789.

Note:

For further options see No. 659940 - 659946.

The guaranteed measuring accuracy of the torque is achieved only once the torque range has been calibrated to DIN EN ISO 6789.

Direction of tightening: Right-hand tightening

Torque measuring accuracy: $\pm 6\%$

Bit socket: F 6.3

Bit socket: D 6,3

Test certificate: Manufacturer's test certificate

Calibration: O1

Torque measuring accuracy: $\pm 6\%$
 Overall length L: 134 mm
 Torque range: 80 - 300 cNm
 Torque range: 0.8 - 3 Nm
 Resolution: 1 cNm
 \varnothing : 34 mm

Technical description

Resolution	1 cNm
\varnothing	34 mm
Display	digital
maximum torque	300 cNm
Torque measuring accuracy	$\pm 6\%$
Bit socket	F 6.3
Bit socket	D 6,3
Torque range	80 - 300 cNm
Torque range	0.8 - 3 Nm
Number of batteries contained	1
Measurement process	Torque
Trigger principle	mechanical short-travel release
Setting the trigger value	digital, adjustable
Reversible reading	Nm
Reversible reading	lbf·in
Adjustable trigger value	adjustable
Standard	DIN EN ISO 6789
Weight	340 g
Feedback	triggering
Connection format	exchangeable blade
Overall length L	134 mm
Series	iTorque®
Calibration	O1

Direction of tightening	Right-hand tightening
Test certificate	Manufacturer's test certificate
Data can be recorded	no
Release signalling	akustisk
Release signalling	haptisk
Measurement technology	mechanical
Power supply	Battery-powered
Battery type	CR1220 MFR FH
chemical composition	Lithium
Torque fixed setting	no
Type of product	Torque screwdriver

Services

Calibration Torque wrench maximum torque 400 Nm	018820 400
Labelling laser-etched Type	018940

Accessories

Bit-holder	659932
Torque interchangeable blade Pozidriv Cross-head size 1	659941 1
Torque interchangeable blade for Phillips Cross-head size 0	659940 0
Torque interchangeable blade for Phillips Cross-head size 1	659940 1
Torque interchangeable blade Pozidriv Cross-head size 0	659941 0