



Torque screwdriver with scale, maximum torque: 1000 cNm



Order data

Order number	659936 1000
GTIN	3148516660480
Item class	63V

Description

Version:

Robust torque screwdriver, adjustable with parallax-free micrometer scale. 1/4 inch internal square at the end of the handle.

Function:

When the set torque is reached the screwdriver triggers and signals clearly (audibly and perceptibly). It is then again immediately ready for use.

Standard:

Geprüft nach DIN EN ISO 6789.

Note:

The guaranteed measuring accuracy of the torque is achieved only once the torque range has been calibrated to DIN EN ISO 6789.

Direction of tightening: Right-hand tightening

Torque measuring accuracy: $\pm 6\%$

Bit socket: D 6,3

Test certificate: Manufacturer's test certificate

Calibration: O1

Torque measuring accuracy: $\pm 6\%$

Overall length L: 168 mm

Torque range: 200 - 1000 cNm

Torque range: 2 - 10 Nm

Scale graduation, 1 graduation =: 50 cNm

Technical description

Display	analogue
Scale graduation, 1 graduation =	50 cNm

maximum torque	1000 cNm
Torque measuring accuracy	±6 %
Bit socket	D 6,3
Torque range	200 - 1000 cNm
Torque range	2 - 10 Nm
Trigger principle	mechanical slip clutch
Setting the trigger value	with adjustment scale
Connection format	Bit holder 1/4 inch
Adjustable trigger value	adjustable
Feedback	triggering
Standard	ISO 6789
Overall length L	168 mm
Reversible reading	Nm
Measurement process	Torque
Calibration	O1
Direction of tightening	Right-hand tightening
Test certificate	Manufacturer's test certificate
Data can be recorded	no
Release signalling	akustisk
Measurement technology	mechanical
Type of product	Torque screwdriver

Services

Calibration Torque wrench maximum torque 400 Nm	018820 400
---	------------

Accessories

Handle with reversible ratchet	659937
--------------------------------	--------