

**Torque screwdriver with scale, maximum torque: 260 cNm****Order data**

Order number	659939 260
GTIN	4560138455111
Item class	66F

Description**Version:**

Torque screwdrivers with over-torque protection for different applications from series production to maintenance work. With a locking mechanism that prevents adjustment of the torque when in use. The hexagon lock shape prevents rolling away. Setting by using micrometer scale. With synthetic resin handle for better grip.

Function:

When the set torque is reached the screwdriver triggers and signals clearly (audibly and perceptibly). It is then again immediately ready for use. The trigger mechanism is unavailable for tightening left-handed threads.

Standard:

Geprüft nach DIN EN ISO 6789.

Note:

The guaranteed measuring accuracy of the torque is achieved only once the torque range has been calibrated to DIN EN ISO 6789.

Direction of tightening: Right-hand tightening

Torque measuring accuracy: ± 3 %

Bit socket: F 6.3

Test certificate: Manufacturer's test certificate

Calibration: O1

Torque measuring accuracy: ± 3 %

Overall length L: 150 mm

Torque range: 60 - 260 cNm

Torque range: 0.6 - 2.6 Nm

Scale graduation, 1 graduation =: 2 cNm

Ø: 30.5 mm

Technical description

Ø	30.5 mm
Torque measuring accuracy	±3 %
maximum torque	260 cNm
Display	analogue
Scale graduation, 1 graduation =	2 cNm
Bit socket	F 6.3
Torque range	60 - 260 cNm
Torque range	0.6 - 2.6 Nm
Reversible reading	Nm
Measurement process	Torque
Connection format	Bit holder 1/4 inch
Weight	270 g
Standard	DIN EN ISO 6789
Setting the trigger value	with adjustment scale
Feedback	triggering
Trigger principle	mechanical slip clutch
Overall length L	150 mm
Adjustable trigger value	adjustable
Calibration	O1
Direction of tightening	Right-hand tightening
Test certificate	Manufacturer's test certificate
Data can be recorded	no
Release signalling	optisk
Release signalling	akustisk
Measurement technology	mechanical
Type of product	Torque screwdriver

Services

Calibration Torque wrench maximum torque 400 Nm

018820 400

Labelling laser-etched Type

018940