



Torque screwdriver with scale, maximum torque: 60 cNm



Order data

| | |
|--------------|---------------|
| Order number | 659939 60 |
| GTIN | 4560138455005 |
| Item class | 66F |

Description

Version:

Torque screwdrivers with over-torque protection for different applications from series production to maintenance work. With a locking mechanism that prevents adjustment of the torque when in use. The hexagon lock shape prevents rolling away. Setting by using micrometer scale. Profiled light metal handle.

Function:

When the set torque is reached the screwdriver triggers and signals clearly (audibly and perceptibly). It is then again immediately ready for use. The trigger mechanism is unavailable for tightening left-handed threads.

Standard:

Geprüft nach DIN EN ISO 6789.

Note:

The guaranteed measuring accuracy of the torque is achieved only once the torque range has been calibrated to DIN EN ISO 6789.

Direction of tightening: Right-hand tightening

Torque measuring accuracy: $\pm 3\%$

Bit socket: F 6.3

Test certificate: Manufacturer's test certificate

Calibration: O1

Torque measuring accuracy: $\pm 3\%$

Overall length L: 110 mm

Torque range: 10 - 60 cNm

Torque range: 0.1 - 0.6 Nm

Scale graduation, 1 graduation =: 0.5 cNm

Ø: 20 mm

Technical description

| | |
|----------------------------------|---------------------------------|
| maximum torque | 60 cNm |
| Ø | 20 mm |
| Display | analogue |
| Scale graduation, 1 graduation = | 0.5 cNm |
| Torque measuring accuracy | ±3 % |
| Bit socket | F 6.3 |
| Torque range | 10 - 60 cNm |
| Torque range | 0.1 - 0.6 Nm |
| Standard | DIN EN ISO 6789 |
| Setting the trigger value | with adjustment scale |
| Feedback | triggering |
| Overall length L | 110 mm |
| Connection format | Bit holder 1/4 inch |
| Weight | 80 g |
| Trigger principle | mechanical slip clutch |
| Adjustable trigger value | adjustable |
| Reversible reading | Nm |
| Measurement process | Torque |
| Calibration | O1 |
| Direction of tightening | Right-hand tightening |
| Test certificate | Manufacturer's test certificate |
| Data can be recorded | no |
| Release signalling | optisk |
| Release signalling | akustisk |
| Measurement technology | mechanical |
| Type of product | Torque screwdriver |

Services

Calibration Torque wrench maximum torque 400 Nm

018820 400

Labelling laser-etched Type

018940