HOLEX

Torque screwdriver with scale, maximum torque: 300 cNm



Order data

Order number	659945 300
GTIN	4045197514011
Item class	62E

Description

Version:

Practical handle for transmission of the required torques without problems. Easy to read micrometer scale, protected against dirt. Lock at the end of the handle against inadvertent adjustment. Interchangeable blade to take 1/4 inch bits included.

Function:

On reaching the set torque value, the screwdriver can be felt and heard to trigger and is then again immediately ready for use.

Application:

For controlled tightening of screws to a pre-set torque.

Standard:

Geprüft nach DIN EN ISO 6789.

Note:

All Wiha interchangeable blades (No. 659940 – 659946) can also be used in the Holex torque screwdriver No. 659945.

The guaranteed measuring accuracy of the torque is achieved only once the torque range has been calibrated to DIN EN ISO 6789.

Direction of tightening: For right- and left-hand tightening

Torque measuring accuracy: ±6 %

Bit socket: D 6,3

Test certificate: Manufacturer's test certificate

Calibration: 01

Torque measuring accuracy: ±6 %

Overall length L: 153 mm

Torque range: 60 - 300 cNm

Torque range: 0.6 - 3 Nm

Scale graduation, 1 graduation =: 10 cNm

Technical description

maximum torque	300 cNm
Display	analogue
Scale graduation, 1 graduation =	10 cNm
Torque measuring accuracy	±6 %
Bit socket	D 6,3
Torque range	60 - 300 cNm
Torque range	0.6 - 3 Nm
Overall length L	153 mm
Weight	300 g
Setting the trigger value	with adjustment scale
Reversible reading	cNm
Reversible reading	Nm
Connection format	Bit holder 1/4 inch
Feedback	triggering
Measurement process	Torque
Standard	DIN EN ISO 6789
Trigger principle	mechanical slip clutch
Adjustable trigger value	adjustable
Calibration	01
Direction of tightening	For right- and left-hand tightening
Test certificate	Manufacturer's test certificate
Data can be recorded	no
Release signalling	acoustic
Release signalling	haptisk
Measurement technology	mechanical
Type of product	Torque screwdriver

Services

Calibration Torque wrench maximum torque 400 Nm	018820 400
Accessories	
Interchangeable blade 1/4 inch	659947
Torque interchangeable blade for Phillips Cross-head size 0	659940 0
Torque interchangeable blade Pozidriv Cross-head size 0	659941 0
Torque interchangeable blade for Phillips Cross-head size 1	659940 1
Torque interchangeable blade Pozidriv Cross-head size 1	659941 1