



## Torque screwdriver with scale, maximum torque: 600 cNm



### Order data

Order number	659945 600
GTIN	4045197514028
Item class	62E

### Description

#### Version:

Practical handle for transmission of the required torques without problems. Easy to read micrometer scale, protected against dirt. Lock at the end of the handle against inadvertent adjustment. Interchangeable blade to take 1/4 inch bits included.

#### Function:

On reaching the set torque value, the screwdriver can be felt and heard to trigger and is then again immediately ready for use.

#### Application:

For controlled tightening of screws to a pre-set torque.

#### Standard:

Geprüft nach DIN EN ISO 6789.

#### Note:

All Wiha interchangeable blades (No. 659940 – 659946) can also be used in the Horex torque screwdriver No. 659945.

The guaranteed measuring accuracy of the torque is achieved only once the torque range has been calibrated to DIN EN ISO 6789.

Direction of tightening: For right- and left-hand tightening

Torque measuring accuracy:  $\pm 6\%$

Bit socket: D 6,3

Test certificate: Manufacturer's test certificate

Calibration: O1

Torque measuring accuracy:  $\pm 6\%$

Overall length L: 153 mm

Torque range: 120 - 600 cNm

Torque range: 1.2 - 6 Nm

Scale graduation, 1 graduation =: 20 cNm

## Technical description

Display	analogue
Scale graduation, 1 graduation =	20 cNm
maximum torque	600 cNm
Torque measuring accuracy	±6 %
Bit socket	D 6,3
Torque range	120 - 600 cNm
Torque range	1.2 - 6 Nm
Adjustable trigger value	adjustable
Trigger principle	mechanical slip clutch
Connection format	Bit holder 1/4 inch
Setting the trigger value	with adjustment scale
Weight	300 g
Reversible reading	cNm
Reversible reading	Nm
Measurement process	Torque
Standard	DIN EN ISO 6789
Feedback	triggering
Overall length L	153 mm
Calibration	O1
Direction of tightening	For right- and left-hand tightening
Test certificate	Manufacturer's test certificate
Data can be recorded	no
Release signalling	acoustic
Release signalling	haptisk
Measurement technology	mechanical
Type of product	Torque screwdriver

## Services

Calibration Torque wrench maximum torque 400 Nm	018820 400
---	------------

**Accessories**

Interchangeable blade 1/4 inch	659947
--------------------------------	--------

Torque interchangeable blade Pozidriv Cross-head size 1	659941 1
---	----------

Torque interchangeable blade Pozidriv Cross-head size 0	659941 0
---	----------

Torque interchangeable blade for Phillips Cross-head size 0	659940 0
---	----------

Torque interchangeable blade for Phillips Cross-head size 1	659940 1
---	----------