

**KANON**
**Torque screwdriver with scale, maximum torque: 300 cNm**

**Order data**

Order number	659949 300
GTIN	4580125347564
Item class	66F

**Description**
**Version:**

Setting using a micrometer scale. Profiled light alloy handle.

**Function:**

When the set torque is reached the screwdriver triggers and signals clearly (audibly and perceptibly). It is then again immediately ready for use.

**Standard:**

Geprüft nach DIN EN ISO 6789.

**Note:**

The guaranteed measuring accuracy of the torque is achieved only once the torque range has been calibrated to DIN EN ISO 6789.

Direction of tightening: For right- and left-hand tightening

Torque measuring accuracy:  $\pm 6\%$

Bit socket: F 6.3

Test certificate: Manufacturer's test certificate

Calibration: O3

Torque measuring accuracy:  $\pm 6\%$

Overall length L: 157 mm

Torque range: 40 - 300 cNm

Torque range: 0.4 - 3 Nm

Scale graduation, 1 graduation =: 1 cNm

Ø: 34 mm

**Technical description**

Display	analogue
Ø	34 mm

maximum torque	300 cNm
Scale graduation, 1 graduation =	1 cNm
Torque measuring accuracy	±6 %
Bit socket	F 6.3
Torque range	40 - 300 cNm
Torque range	0.4 - 3 Nm
Feedback	triggering
Connection format	Bit holder 1/4 inch
Adjustable trigger value	adjustable
Reversible reading	cNm
Overall length L	157 mm
Standard	DIN EN ISO 6789
Trigger principle	mechanical short-travel release
Setting the trigger value	with adjustment scale
Measurement process	Torque
Weight	214 g
Calibration	O3
Direction of tightening	For right- and left-hand tightening
Test certificate	Manufacturer's test certificate
Data can be recorded	no
Measurement technology	mechanical
Release signalling	akustisk
Release signalling	haptisk
Type of product	Torque screwdriver

## Services

Calibration Torque wrench both ends maximum torque 400/2 Nm	018821 400/2
Labelling laser-etched Type	018940

