

**KANON**
**Torque screwdriver with scale, maximum torque: 500 cNm**

**Order data**

Order number	659949 500
GTIN	4580125347571
Item class	66F

**Description**
**Version:**

Setting using a micrometer scale. Profiled light alloy handle.

**Function:**

When the set torque is reached the screwdriver triggers and signals clearly (audibly and perceptibly). It is then again immediately ready for use.

**Standard:**

Geprüft nach DIN EN ISO 6789.

**Note:**

The guaranteed measuring accuracy of the torque is achieved only once the torque range has been calibrated to DIN EN ISO 6789.

Direction of tightening: For right- and left-hand tightening

Torque measuring accuracy:  $\pm 6\%$

Bit socket: F 6.3

Test certificate: Manufacturer's test certificate

Calibration: O3

Torque measuring accuracy:  $\pm 6\%$

Overall length L: 200 mm

Torque range: 100 - 500 cNm

Torque range: 1 - 5 Nm

Scale graduation, 1 graduation =: 2.5 cNm

Ø: 40 mm

**Technical description**

Display	analogue
Ø	40 mm

maximum torque	500 cNm
Scale graduation, 1 graduation =	2.5 cNm
Torque measuring accuracy	±6 %
Bit socket	F 6.3
Torque range	100 - 500 cNm
Torque range	1 - 5 Nm
Reversible reading	cNm
Standard	DIN EN ISO 6789
Weight	436 g
Measurement process	Torque
Connection format	Bit holder 1/4 inch
Overall length L	200 mm
Trigger principle	mechanical short-travel release
Setting the trigger value	with adjustment scale
Feedback	triggering
Adjustable trigger value	adjustable
Calibration	O3
Direction of tightening	For right- and left-hand tightening
Test certificate	Manufacturer's test certificate
Data can be recorded	no
Release signalling	akustisk
Release signalling	haptisk
Measurement technology	mechanical
Type of product	Torque screwdriver

## Services

Calibration Torque wrench both ends maximum torque 1000/2 Nm	018821 1000/2
Labelling laser-etched Type	018940
	018831 1000/2

DAkKS calibration Torque wrench both ends maximum  
torque 1000/2 Nm

---