

KANON
Torque screwdriver with scale, maximum torque: 60 cNm

Order data

Order number	659949 60
GTIN	4580125347533
Item class	66F

Description
Version:

Setting using a micrometer scale. Profiled light alloy handle.

Function:

When the set torque is reached the screwdriver triggers and signals clearly (audibly and perceptibly). It is then again immediately ready for use.

Standard:

Geprüft nach DIN EN ISO 6789.

Note:

The guaranteed measuring accuracy of the torque is achieved only once the torque range has been calibrated to DIN EN ISO 6789.

Direction of tightening: For right- and left-hand tightening

Torque measuring accuracy: $\pm 6\%$

Bit socket: F 6.3

Test certificate: Manufacturer's test certificate

Calibration: O3

Torque measuring accuracy: $\pm 6\%$

Overall length L: 110 mm

Torque range: 5 - 60 cNm

Torque range: 0.05 - 0.6 Nm

Scale graduation, 1 graduation =: 0.5 cNm

Ø: 25 mm

Technical description

Ø	25 mm
Display	analogue

maximum torque	60 cNm
Scale graduation, 1 graduation =	0.5 cNm
Torque measuring accuracy	±6 %
Bit socket	F 6.3
Torque range	5 - 60 cNm
Torque range	0.05 - 0.6 Nm
Connection format	Bit holder 1/4 inch
Overall length L	110 mm
Feedback	triggering
Measurement process	Torque
Reversible reading	cNm
Adjustable trigger value	adjustable
Setting the trigger value	with adjustment scale
Standard	DIN EN ISO 6789
Trigger principle	mechanical short-travel release
Weight	99 g
Calibration	O3
Direction of tightening	For right- and left-hand tightening
Test certificate	Manufacturer's test certificate
Data can be recorded	no
Release signalling	akustisk
Release signalling	haptisk
Measurement technology	mechanical
Type of product	Torque screwdriver

Services

Calibration Torque wrench both ends maximum torque 400/2 Nm	018821 400/2
Labelling laser-etched Type	018940

