



Torque screwdriver, Type: 6IP



Order data

| | |
|--------------|---------------|
| Order number | 659950 6IP |
| GTIN | 4013288093387 |
| Item class | 63F |

Description

Version:

Proven Kraftform handle, from 5 Nm with pistol grip. Every screwdriver is preset to the **correct torque for each size of screw**.

A sealing ring protects the mechanism in the handle from interference and inadvertent adjustment. Drive size and torque are stamped on the end of the handle.

When the set torque is reached the screwdriver triggers with clearly audible and perceptible signals. It is **not possible to tighten the screw any further**.

Size 2 – 4 for socket head screws.

Size TX6 – TX20 for screws with **Torx® profile**.

Size 6IP – 20IP for screws with **Torx Plus® profile**.

Application:

Ideal for fitting indexable inserts.

Standard:

Geprüft nach DIN EN ISO 6789.

Note:

The guaranteed measuring accuracy of the torque is achieved only once the torque range has been calibrated to DIN EN ISO 6789.

Direction of tightening: Right-hand tightening

Torque measuring accuracy: $\pm 10\%$

Torque measuring accuracy: $\pm 10\%$

Overall length L: 175 mm

Blade length: 65 mm

set torque: 0.6 Nm

set torque: 60 cNm

Technical description

| | |
|---------------------------|------------------------|
| Blade length | 65 mm |
| Torque measuring accuracy | ±10 % |
| set torque | 60 cNm |
| set torque | 0.6 Nm |
| Adjustable trigger value | non-adjustable |
| Setting the trigger value | pre-set |
| Measurement process | Torque |
| Connection format | fixed |
| Overall length L | 175 mm |
| Reversible reading | cNm |
| Standard | DIN EN ISO 6789 |
| Feedback | triggering |
| Trigger principle | mechanical slip clutch |
| Direction of tightening | Right-hand tightening |
| Data can be recorded | no |
| Release signalling | akustisk |
| Release signalling | haptisk |
| Measurement technology | mechanical |
| Torque fixed setting | yes |
| Type of product | Torque screwdriver |