



## Torque screwdriver without scale, ESD, maximum torque: 120 cNm



### Order data

Order number	659954 120
GTIN	4013288179487
Item class	63F

### Description

#### Version:

**Kraftform** handle for easy transmission of the required torque. With **Rapidaptor** quick-change holder for 1/4 inch bits with C 6.3 and E 6.3 shank.

The torque can be set using a torque analyser (No. 654300 – 654460) and a 7AF hexagon screwdriver (10AF for size 600). **The torque screwdrivers are factory-set to the most frequently used torque setting.**

Tool handle made of conductive plastic, **suitable for ESDs.**

#### Function:

When the set torque is reached the screwdriver triggers, with clearly audible and perceptible signals. The triggering torque is unrestricted.

#### Standard:

Geprüft nach DIN EN ISO 6789.

#### Note:

The guaranteed measuring accuracy of the torque is achieved only once the torque range has been calibrated to DIN EN ISO 6789.

Rapidaptor free-running coupling shank available from our eShop (No. 675035 size 6.3F).  
electrical insulation: EGB/ESD

Direction of tightening: Right-hand tightening

Torque measuring accuracy:  $\pm 6\%$

Bit socket: D 6,3

Bit socket: F 6.3

Test certificate: Manufacturer's test certificate

Calibration: O6

Torque measuring accuracy:  $\pm 6\%$

Overall length L: 155 mm

set torque: 0.3 Nm

Torque range: 30 - 120 cNm

Torque range: 0.3 - 1.2 Nm

1 turn (360°) corresponds to: 10 cNm

## Technical description

set torque	0.3 Nm
1 turn (360°) corresponds to	10 cNm
Torque measuring accuracy	±6 %
Torque range	30 - 120 cNm
maximum torque	120 cNm
Torque range	0.3 - 1.2 Nm
Bit socket	D 6,3
Bit socket	F 6.3
Connection format	Bit holder 1/4 inch
Overall length L	155 mm
Adjustable trigger value	forudindstillet
Trigger principle	mechanical short-travel release
Measurement process	Torque
Standard	DIN EN ISO 6789
Reversible reading	cNm
Setting the trigger value	without adjustment scale (requires a testing device)
Feedback	triggering
Weight	122 g
Calibration	O6
Direction of tightening	Right-hand tightening
Test certificate	Manufacturer's test certificate
Data can be recorded	no
Measurement technology	mechanical
Release signalling	akustisk
Release signalling	haptisk

electrical insulation	EGB/ESD
Torque fixed setting	no
Type of product	Torque screwdriver

## Services

Adjustment Torque wrench without scale	018890
Calibration and adjustment Torque wrench without scale maximum torque 400 Nm	018891 400