



Torque multiplier in a plastic case, maximum output capacity: 2000 Nm



Order data

Order number	659980 2000
GTIN	2050001691545
Item class	66D

Description

Version:

Mechanical manual torque multiplier for controlled screw tightening. Multiplier and support of high-quality steel. With overload shut-off to protect the transmission. **Input drive** with internal square socket for drive tools such as a ratchet, T-handle, torque wrench. It is sensible to operate the device with a torque wrench, so that the maximum load and the screw torque values can be checked. **Output drive** with external square for holding sockets (preferably use impact sockets due to the high torques).

Extremely precisely machined transmissions with ground gears and honed bores guarantee exact and consistently reproducible torque multiplication. Unique accuracy of not less than ± 4 %. Very compact and lightweight design, exceptionally long working life, and low maintenance.

Advantage:

Torque multipliers allow the transmission of higher torques with a correspondingly shorter lever arm.

Note:

Alternative reaction plates for No. 659980 size 2000 and 7000 available on request. No. 659980 size 2000 available on request with electronic measured value sensors.

Test certificate: Manufacturer's test certificate

Length L: 201.5 mm

Height H: 182.3 mm

maximum input capacity: 74 Nm

Torque multiplication / effective force multiplication: 1:27
recommended torque wrench / tightening range: 100 Nm
Number of supports (reaction plates): 1

Technical description

Torque multiplication / effective force multiplication	1:27
recommended torque wrench / tightening range	100 Nm
Number of supports (reaction plates)	1
Square drive	1/2 inch
Drive square	1 inch
maximum output capacity	2000 Nm
Weight	3.2 kg
Overload protection	yes
Ø D	72 mm
maximum input capacity	74 Nm
Non-return valve	yes
Length L	201.5 mm
Height H	182.3 mm
Measurement technology	mechanical
Measuring accuracy	4 %
Test certificate	Manufacturer's test certificate
Type of product	Torque Wrench