



## Screwdriver for slot-head, with 2-component SwissGrip handle ESD, Blade width b: 2,5 mm



### Order data

Order number	660050 2,5
GTIN	7610733269068
Item class	63E

### Description

#### Version:

Versatile, robust screwdriver with taper blade.

The special surface structure allows transmission of high torques, even with wet or oily hands.

**Blade** of chrome vanadium special alloy combining maximum hardness and exceptional toughness.

Surface nickel-plated and chrome-plated, with black plane parallel stepped tip.

Tool handle made of conductive plastic, **suitable for ESDs**.

**SwissGrip-power grip** with non-allergenic elastomer coating and a core of particularly tough and impact-resistant polypropylene.

#### Advantage:

- **Stepped plane parallel tips provide full-surface instead of linear contact, enabling higher torque transmission.**
- **No cam-out effect.**
- **Tips perfectly fit standard and non-standard screw slot sizes.**
- **Smooth, burr-free rounding of the end of the handle prevents friction in the palm of the hand.**
- **Rounded ergonomic shape with comfortable easy-grip surface ensures non-fatiguing working and high torque transmission.**
- **Non-roll flats.**
- **Marked with drive symbol and size.**

#### Application:

For repair and assembly work, for loosening tight screws etc.

electrical insulation: EGB/ESD

Blade designation: 0

Tip thickness a: 0.4 mm

Blade length: 80 mm

overall length: 160 mm

## Technical description

Blade designation	0
Blade length	80 mm
Blade width b	2.5 mm
overall length	160 mm
Tip thickness a	0.4 mm
electrical insulation	EGB/ESD
Drive profile	Slot-head screwdriver
Type of product	Screwdrivers