

Slim screwdriver for PlusMinus screws, Classic fully insulated, Profile size: 1



Order data

Order number	668392 1
GTIN	7610733278435
Item class	63E

Description

Version:

Handle and blade **fully insulated up to 1000 V to DIN EN 60900 / VDE 0682-201.** Each of these screwdrivers is individually tested in a water bath for insulation breakdown under high voltage. **Slim handle** with a non-allergenic elastomer coating and a core of particularly tough and impact-resistant polypropylene. Due to its special surface structure, the grip is non-slip even with

oily or wet hands.

Blade of PB Swiss Tools special alloy combines maximum hardness with exceptional toughness. **Reduced blade** \varnothing **with integral protective insulation** for deep-lying screws and spring elements (blade \varnothing = insulation \varnothing near the tip of the blade).

Application:

For use at voltages up to 1000 V.

The screwdriver drive tip fits perfectly into the **PlusMinus screws (combination Pozidriv / slothead)**, which are primarily used in electrical installation components.

Profile Pozidriv – slot head: $1 - 0.7 \times 4.5$

Blade length: 80 mm overall length: 175 mm

Technical description

Profile Pozidriv – slot head	1 – 0.7×4.5
overall length	175 mm
Profile size	1
Blade length	80 mm
Standard	DIN EN 60900 / VDE 0682-201

Data sheet

⚠ Hoffmann Group

Drive profile

Combination profile screwdriver Pozidriv/slot-head