

Slim screwdriver for PlusMinus screws, Classic fully insulated, Profile size: 2



Order data

Order number	668392 2
GTIN	7610733278442
Item class	63E

Description

Version:

Handle and blade **fully insulated up to 1000 V to DIN EN 60900 / VDE 0682-201.** Each of these screwdrivers is individually tested in a water bath for insulation breakdown under high voltage. **Slim handle** with a non-allergenic elastomer coating and a core of particularly tough and impact-resistant polypropylene. Due to its special surface structure, the grip is non-slip even with oily or wet hands.

Blade of PB Swiss Tools special alloy combines maximum hardness with exceptional toughness. **Reduced blade** \varnothing **with integral protective insulation** for deep-lying screws and spring elements (blade \varnothing = insulation \varnothing near the tip of the blade).

Application:

For use at voltages up to 1000 V.

The screwdriver drive tip fits perfectly into the **PlusMinus screws (combination Pozidriv / slothead)**, which are primarily used in electrical installation components.

Profile Pozidriv – slot head: $2 - 1.0 \times 6$

Blade length: 100 mm overall length: 205 mm

Technical description

Blade length	100 mm
Profile size	2
Profile Pozidriv – slot head	2 – 1.0×6
overall length	205 mm
Standard	DIN EN 60900 / VDE 0682-201

Data sheet

⚠ Hoffmann Group

Drive profile

Combination profile screwdriver Pozidriv/slot-head