

Combination tap bits set in a sturdy box, 7 pieces



Order data

| Order number | 676308 |
|--------------|---------------|
| GTIN | 4013288101594 |
| Item class | 63H |

Description

Version:

1/4 inch hexagon shank to DIN 3126 C 6.3.

Advantage:

Quick and uncomplicated changes between drill, countersink, and screw bits.

Application:

Ideal for repair and assembly work in mobile situations.

1 tool for 3 operations:

drill tapping hole – tap thread – deburr / countersink.

For use in power drills with forward and reverse drive.

Content:

Combination tap bits: No. 676306 1 pc. each size M3; M4; M5; M6; M8; M10 "Rapidaptor" coupling shank: 1 pc. similar to No. 675020 size 6.3K (without magnet) Application for type of drilling: up to $1\times D$ for through holes

Technical description

| Thread type | M |
|---------------|-----|
| Tool material | HSS |

| Point angle | 60 degrees |
|----------------------------------|-----------------------------|
| Tolerance class | ISO 2 6H |
| Flank angle | 60 degrees |
| Application for type of drilling | up to 1×D for through holes |
| Number of pieces | 7 |

Accessories

| HSS combination tap bit for threads M8 | 676306 M8 |
|--|-------------|
| HSS combination tap bit for threads M5 | 676306 M5 |
| HSS combination tap bit for threads M4 | 676306 M4 |
| Shank with magnet / quick-change coupling Hexagon shank 6,3K | 675020 6,3K |
| HSS combination tap bit for threads M6 | 676306 M6 |
| HSS combination tap bit for threads M3 | 676306 M3 |
| HSS combination tap bit for threads M10 | 676306 M10 |