

Diagonal side cutter, chrome-plated VDE dip insulated, overall length: 200 mm



Order data

Order number	723535 200
GTIN	4003773018414
Item class	73F

Description

Version:

Heavy-duty head, induction hardened cutting edges (approx. 64 HRC), laid-on joint with no play. Plastic-coated handles to DIN EN 60900 / VDE 0682-201 for working at voltages up to 1000 V

Jaws chrome-plated, plastic coated handles, dip insulated.

Standard:

DIN ISO 5749

Material:

Chrome vanadium steel, drop-forged and oil-hardened.

Cutting capacity soft wire up to \emptyset : 4.2 mm Cutting capacity hard wire up to \emptyset : 3 mm Cutting capacity piano wire up to \emptyset : 2.5 mm

Technical description

overall length	200 mm
Cutting capacity hard wire up to \varnothing	3 mm
Cutting capacity soft wire up to \emptyset	4.2 mm
Cutting capacity piano wire up to \varnothing	2.5 mm
Standard	DIN EN 60900 / VDE 0682-201
Standard	DIN ISO 5749

Handle	plastic coated
Manufacturing process	Cutting edges induction hardened (approx. 64 HRC)
Material	Chrome vanadium steel, drop- forged and oil-hardened
Surface	chrome-plated
Heavy-duty diagonal side cutter	no
with selectable return spring	no