KNIPEX

Diagonal side cutter, chrome-plated VDE dip insulated, overall length: 250 mm



Order data

Order number	723535 250
GTIN	4003773018421
Item class	73F

Description

Version:

Heavy-duty head, induction hardened cutting edges (approx. 64 HRC), laid-on joint with no play.
Plastic-coated handles to DIN EN 60900 / VDE 0682-201 for working at voltages up to 1000 V
Jaws chrome-plated, plastic coated handles, dip insulated.
Standard:
DIN ISO 5749
Material:
Chrome vanadium steel, drop-forged and oil-hardened.
Cutting capacity soft wire up to Ø: 4.6 mm
Cutting capacity hard wire up to Ø: 3.5 mm
Cutting capacity piano wire up to Ø: 3 mm

Technical description

Cutting capacity soft wire up to Ø	4.6 mm
Cutting capacity piano wire up to \varnothing	3 mm
Cutting capacity hard wire up to \varnothing	3.5 mm
overall length	250 mm
Standard	DIN EN 60900 / VDE 0682-201
Standard	DIN ISO 5749

Handle	plastic coated
Manufacturing process	Cutting edges induction hardened (approx. 64 HRC)
Material	Chrome vanadium steel, drop- forged and oil-hardened
Surface	chrome-plated
Heavy-duty diagonal side cutter	no
with selectable return spring	no