



Heavy-duty side cutter, polished, with return spring, overall length: 180 mm



Order data

| Order number | 725230 180 |
|--------------|---------------|
| GTIN | 4003773060192 |
| Item class | 73F |

Description

Version:

Heavy-duty head with additionally induction hardened cutting edges (approx. 64 HRC). Laid-on joint. **With return spring that can be engaged / disengaged.**

Pliers chemically blacked, head bright polished, handles with multi-component covering. High cutting performance due to optimum leverage.

Standard:

DIN ISO 5749

Material:

Chrome vanadium steel, drop-forged and oil-hardened.

Cutting capacity soft wire up to Ø: 3.8 mm Cutting capacity hard wire up to Ø: 2.7 mm Cutting capacity piano wire up to Ø: 2.2 mm

Technical description

| Cutting capacity soft wire up to \varnothing | 3.8 mm |
|---|---|
| Cutting capacity piano wire up to \varnothing | 2.2 mm |
| overall length | 180 mm |
| Cutting capacity hard wire up to \varnothing | 2.7 mm |
| Norm | DIN ISO 5749 |
| Handle | Multi-component covering |
| Manufacturing process | Cutting edges induction hardened (approx. 64 HRC) |



| Material | Chrome vanadium steel, drop- forged and oil-hardened |
|---------------------------------|---|
| Surface | chemically blackened, head bright polished |
| Heavy-duty diagonal side cutter | no |
| with selectable return spring | yes |