



Diagonal side cutter, chrome-plated VDE dip insulated, overall length: 160 mm



Order data

| | |
|--------------|---------------|
| Order number | 725335 160 |
| GTIN | 4003773018155 |
| Item class | 73F |

Description

Version:

Slim shape with induction hardened cutting edges (approx. 62 HRC). **Plastic-coated handles to DIN EN 60900 / VDE 0682-201 for working at voltages up to 1000 V.**

Jaws chrome-plated, plastic coated handles, **dip insulated.**

Standard:

DIN ISO 5749

Material:

Special tool steel, drop-forged, and oil-hardened.

Cutting capacity soft wire up to Ø: 4 mm

Cutting capacity hard wire up to Ø: 2 mm

Technical description

| | |
|------------------------------------|---|
| overall length | 160 mm |
| Cutting capacity soft wire up to Ø | 4 mm |
| Cutting capacity hard wire up to Ø | 2 mm |
| Standard | DIN EN 60900 / VDE 0682-201 |
| Standard | DIN ISO 5749 |
| Handle | plastic coated, dip insulated |
| Manufacturing process | Cutting edges induction hardened (approx. 62 HRC) |

| | |
|---------------------------------|--|
| Material | Special tool steel, drop-forged and oil-hardened |
| Surface | chrome-plated |
| Heavy-duty diagonal side cutter | no |
| with selectable return spring | no |