



UNIBOLT® bolt cutter, overall length: 910 mm



Order data

Order number	733500 910
GTIN	4005887563507
Item class	73L

Description

Version:

Cutter head with compound action and universal jaws. Eccentric screws allow precise and easy adjustment of the blades. Drop forged, centre stop with extra-large shock-absorbing zone; painted tubular handles.

Application:

For cutting normal and high-tensile steels up to 48 HRC (about 1600 N/mm² tensile strength).

Material:

Special tool steel jaws, blades induction hardened.

Spare part:

Spare jaws No. 734110.

for round steel bar up to 19 HRC and 800 N/mm² up to Ø: 13 mm for round steel bar up to 40 HRC and 1200 N/mm² up to Ø: 11 mm for round steel bar up to 48 HRC and 1600 N/mm² up to Ø: 9 mm

Technical description

for round steel bar up to 19 HRC and 800 N/mm 2 up to \varnothing	13 mm
overall length	910 mm
for round steel bar up to 48 HRC and 1600 N/mm 2 up to $\ensuremath{\mathcal{O}}$	9 mm
for round steel bar up to 40 HRC and 1200 N/mm 2 up to Ø	11 mm
Cutting capacity	<48 HR
with over-expansion guard	yes
Manufacturer's designation	UNIBOLT®



Blade	induction hardened
Material	Special steel, drop forged
Surface	painted red
with adjustment screw	yes

Accessories

Spare jaws complete with screws overall length 910 mm 734110 910