

 **HALDER**
**SIMPLEX soft-faced hammer with composite rubber inserts, black, Body Ø /  
Material: 50A mm**

**Order data**

Order number	752800 50A
GTIN	4030618300380
Item class	73W

**Description**
**Version:**

Sturdy, two-piece clamp housing with two exchangeable striking inserts. Suitable inserts are available for various types of work.

All insert types can also be combined with each other.

**Soft-faced hammers and driving mallets:** Aluminium or annealed cast iron housing; wooden handle.

**Application:**

Size **A** = **Aluminium housing:** For light work, e.g. positioning.

Size **G** = **Annealed cast iron housing:** For heavy, powerful blows, e.g. driving machine parts into position etc.

**Spare part:**

Spare handle available under No. 753400 and soft-faced hammer housing under No. 753310.

**Note:**

Size codes **A** = Aluminium housing; **G** = Annealed cast iron housing.

Head length with inserts: 135 mm

Striking face Ø of the inserts: 50 mm

Handle length: 310 mm

Overall length: 365 mm

Weight: 0.74 kg

**Technical description**

Overall length	365 mm
Head length with inserts	135 mm

Striking face Ø of the inserts	50 mm
Handle length	310 mm
Material of body	Aluminium
Weight	0.74 kg
Material of the handle	wood
Series	SIMPLEX soft-faced hammer
Material of insert	Rubber composition, medium hard
Colour	black

## Accessories

SIMPLEX soft-faced hammer housing without inserts, without handle Body Ø / Material 50A mm	753310 50A
SIMPLEX soft-faced hammer, plastic insert for Hammer head Ø 50 mm	753600 50
SIMPLEX soft-faced hammer housing without inserts, without handle Body Ø / Material 50G mm	753310 50G
SIMPLEX soft-faced hammer, super-plastic insert for Hammer head Ø 50 mm	753700 50
SIMPLEX soft-faced hammer, soft metal insert for Hammer head Ø 50 mm	754000 50
SIMPLEX soft-faced hammer, spare handle for soft-faced hammer 50	753400 50
SIMPLEX soft-faced hammer, rubber composition insert for Hammer head Ø 50 mm	753500 50
SIMPLEX soft-faced hammer, soft plastic TPE insert for Hammer head Ø 50 mm	753450 50