

SIMPLEX soft-faced hammer with composite rubber inserts, black, Body Ø / Material: 50G mm



Order data

Order number	752800 50G
GTIN	4030618300069
Item class	73W

Description

Version:

Sturdy, two-piece clamp housing with two exchangeable striking inserts. Suitable inserts are available for various types of work.

All insert types can also be combined with each other.

Soft-faced hammers and driving mallets: Aluminium or annealed cast iron housing; wooden handle.

Application:

Size **A** = **Aluminium housing:** For light work, e.g. positioning.

Size **G** = **Annealed cast iron housing:** For heavy, powerful blows, e.g. driving machine parts into position etc.

Spare part:

Spare handle available under No. 753400 and soft-faced hammer housing under No. 753310. **Note:**

Size codes \mathbf{A} = Aluminium housing; \mathbf{G} = Annealed cast iron housing.

Head length with inserts: 135 mm

Striking face Ø of the inserts: 50 mm

Handle length: 310 mm

Overall length: 365 mm

Weight: 1.15 kg

Technical description

Striking face Ø of the inserts	50 mm
Material of the handle	wood

Weight	1.15 kg
Head length with inserts	135 mm
Material of body	Cast steel
Overall length	365 mm
Handle length	310 mm
Series	SIMPLEX soft-faced hammer
Material of insert	Rubber composition, medium hard
Colour	black

Accessories

SIMPLEX soft-faced hammer, rubber composition insert for Hammer head \varnothing 50 mm	753500 50
SIMPLEX soft-faced hammer housing without inserts, without handle Body \emptyset / Material 50A mm	753310 50A
SIMPLEX soft-faced hammer, plastic insert for Hammer head \varnothing 50 mm	753600 50
SIMPLEX soft-faced hammer, soft metal insert for Hammer head \varnothing 50 mm	754000 50
SIMPLEX soft-faced hammer, super-plastic insert for Hammer head \varnothing 50 mm	753700 50
SIMPLEX soft-faced hammer, spare handle for soft-faced hammer 50	753400 50
SIMPLEX soft-faced hammer, soft plastic TPE insert for Hammer head \varnothing 50 mm	753450 50
SIMPLEX soft-faced hammer housing without inserts, without handle Body Ø / Material 50G mm	753310 50G