A HALDER

SIMPLEX soft-faced hammer with plastic inserts, red, Body \varnothing / Material: 50G mm



Order data

Order number	752900 50G
GTIN	4030618300151
Item class	73W

Description

Version:

Sturdy, two-piece clamp housing with two exchangeable striking inserts. Suitable inserts are available for various types of work.

All insert types can also be combined with each other.

Soft-faced hammers and driving mallets: Aluminium or annealed cast iron housing; wooden handle.

Application:

Size **A** = **Aluminium housing:** For light work, e.g. positioning.

Size **G** = **Annealed cast iron housing:** For heavy, powerful blows, e.g. driving machine parts into position etc.

Spare part:

Spare handle available under No. 753400 and soft-faced hammer housing under No. 753310.

Note:

Size codes \mathbf{A} = Aluminium housing; \mathbf{G} = Annealed cast iron housing.

Head length with inserts: 135 mm Striking face \varnothing of the inserts: 50 mm

Handle length: 310 mm Overall length: 365 mm

Weight: 1.12 kg

Technical description

Overall length	365 mm
Striking face Ø of the inserts	50 mm

Handle length	310 mm
Material of body	Cast steel
Head length with inserts	135 mm
Weight	1.12 kg
Material of the handle	wood
Series	SIMPLEX soft-faced hammer
Material of insert	Plastic, hard
Colour	red

Accessories

SIMPLEX soft-faced hammer housing without inserts, without handle Body \varnothing / Material 50G mm	753310 50G
SIMPLEX soft-faced hammer, spare handle for soft-faced hammer 50	753400 50
SIMPLEX soft-faced hammer, super-plastic insert for Hammer head \varnothing 50 mm	753700 50
SIMPLEX soft-faced hammer housing without inserts, without handle Body Ø / Material 50A mm	753310 50A
SIMPLEX soft-faced hammer, soft metal insert for Hammer head \varnothing 50 mm	754000 50
SIMPLEX soft-faced hammer, rubber composition insert for Hammer head \varnothing 50 mm	753500 50
SIMPLEX soft-faced hammer, plastic insert for Hammer head Ø 50 mm	753600 50
SIMPLEX soft-faced hammer, soft plastic TPE insert for Hammer head \varnothing 50 mm	753450 50