A HALDER

SIMPLEX soft-faced hammer without inserts, with handle, Body \varnothing / Material: 40A mm



Order data

Order number	753300 40A
GTIN	2050001008411
Item class	73W

Description

Version:

Sturdy, two-piece clamp housing with two exchangeable striking inserts. Suitable inserts are available for various types of work.

All insert types can also be combined with each other.

Soft mallets and driving mallets: Aluminium or annealed cast iron housing; wooden handle. **Soft-faced hammers and driving mallets:** Aluminium or annealed cast iron housing; wooden handle.

Application:

Size **A** = **Aluminium housing:** For light work, e.g. positioning.

Size **G** = **Annealed cast iron housing:** For heavy, powerful blows, e.g. driving machine parts into position etc.

Spare part:

Spare handle available under No. 753400 and soft-faced hammer housing under No. 753310.

Note:

Size codes \mathbf{A} = Aluminium housing; \mathbf{G} = Annealed cast iron housing.

Head length with inserts: 110 mm Striking face \varnothing of the inserts: 40 mm

Handle length: 280 mm Overall length: 330 mm

Technical description

Body ∅	40 mm
Striking face Ø of the inserts	40 mm



Overall length	330 mm
Handle length	280 mm
Material of body	Aluminium
Head length with inserts	110 mm
Series	SIMPLEX soft-faced hammer

Accessories

SIMPLEX soft-faced hammer, soft plastic TPE insert for Hammer head \varnothing 40 mm	753450 40
SIMPLEX soft-faced hammer, super-plastic insert for Hammer head \varnothing 40 mm	753700 40
SIMPLEX soft-faced hammer, soft metal insert for Hammer head \varnothing 40 mm	754000 40
SIMPLEX soft-faced hammer housing without inserts, without handle Body Ø / Material 40G mm	753310 40G
SIMPLEX soft-faced hammer, spare handle for soft-faced hammer 40	753400 40
SIMPLEX soft-faced hammer, rubber composition insert for Hammer head \varnothing 40 mm	753500 40
SIMPLEX soft-faced hammer, plastic insert for Hammer head Ø 40 mm	753600 40
SIMPLEX soft-faced hammer housing without inserts, without handle Body Ø / Material 40A mm	753310 40A