



Pneumatic-hydraulic pop rivet tool TAURUS®, Type: 2



Order data

Order number

770512 2

GTIN

4007081570008

Item class

74A

Description

Version:

Operating pressure 5 – 7 bar. Removable rivet pin capture box.

Advantage:

The **gripping jaw system** ensures very long tool life and a non-slip grip on the rivet spigot. Low compressed air consumption due to two-phase operation: for setting **and** for lifting away the broken-off tail. Very quick operating cycle.

Supplied with:

Assembly spanners 12 / 14 AF and 14 / 17 AF.

1 bottle hydraulic oil 100 ml and 1 oil refill container. Including nozzles 17/24, 17/27, 17/29, 17/32.

Tool stroke: 18 mm

Setting force at 5 bar: 9000 N

Air consumption per rivet: 2.3 l

Hose connection: 6 mm

Hose connection: 1/4 inch

maximum mandrel Ø: 3.2 mm

Technical description

for pop rivets steel / aluminium up to

6 mm

Setting force at 5 bar	9000 N
Tool stroke	18 mm
maximum mandrel Ø	3.2 mm
Hose connection	6 mm
Weight	1.6 kg
for pop rivets in all materials up to	5 mm
Air consumption per rivet	2.3 l
Hose connection	1/4 inch
Type of product	Pop riveter