

Carbide-tipped hammer drill SDS-plus, Øxoverall length: 16X450 mm



Order data

Order number	789040 16X450
GTIN	4062406135829
Item class	71C

Description

Version:

Drill head with square cross-section. **4x90° geometry** with specially developed **equal height tips** and stable shoulders ensure precisely dimensioned holes for professional setting of anchors and secure plug attachment. 4-flute drilling heads for smooth drilling with low vibration and optimum guidance in the drilled hole. **Radially** shaped **reinforcement protection**: prevents jamming when hitting reinforcements and increases the working life. Sturdy **single-piece** carbide head with 4 cutters, inserted as a solid item in the core of the drill. Significantly reduced risk of breakage.

Advantage:

- · Short spiral starts ensure a smooth evacuation of the drill dust.
- · Wear marks: for evaluation whether the tool is still suitable for drilling holes suitable for insertion of plugs.
- · 4×4 design permits a precise radial run-out and minimise wear and loss of frictional grip. Application:

For drilling concrete, natural stone, and masonry – with very high drilling comfort.

Shank: SDS Plus Flute length: 400 mm

Technical description

Flute length	400 mm
overall length	450 mm
Ø	16 mm
Tool material	Carbide
Use with impact / without impact	Impact drilling

Shank	SDS Plus
Type of product	Masonry drill