Garant

Carbide-tipped hammer drill SDS-plus, Ø×overall length: 30X450 mm

-155550.

Order data

Order number	789040 30X450
GTIN	4062406135874
Item class	71C

Description

Version:

Drill head with square cross-section. **4×90° geometry** with specially developed **equal height tips** and stable shoulders ensure precisely dimensioned holes for professional setting of anchors and secure plug attachment. 4-flute drilling heads for smooth drilling with low vibration and optimum guidance in the drilled hole. **Radially** shaped **reinforcement protection**: prevents jamming when hitting reinforcements and increases the working life. **3-piece** sturdy carbide head with reinforced centre point. Sturdy auxiliary cutting edges support the advance and thus permit sustained high performance and constant precision.

Advantage:

- · Short spiral starts ensure a smooth evacuation of the drill dust.
- Wear marks: for evaluation whether the tool is still suitable for drilling holes suitable for insertion of plugs.
- $\cdot\,$ 4×4 design permits a precise radial run-out and minimise wear and loss of frictional grip. Application:

For drilling concrete, natural stone, and masonry – with very high drilling comfort. Shank: SDS Plus Flute length: 400 mm

Technical description

Ø	30 mm
overall length	450 mm
Flute length	400 mm
Tool material	Carbide
Use with impact / without impact	Impact drilling

Shank	SDS Plus
Type of product	Masonry drill