



## Carbide-tipped hammer drill, SDS-max, Ø×overall length: 28X570 mm



### Order data

|              |               |
|--------------|---------------|
| Order number | 789200 28X570 |
| GTIN         | 4002395374373 |
| Item class   | 76G           |

### Description

#### Version:

#### Special carbide insert geometry for longer tool lives.

TARGET TIP TECHNOLOGY – more severely angled tip: More precise drilling, no slipping on the surface, aggressive drilling in concrete steel and faster drilling speed. PGM-certified – approves precise drilled holes suitable for plugs, both for chemical and mechanical anchors. Large flute channels for quick evacuation of waste material, resulting in less friction.

Drill head with square cross section from Ø 16 mm.

#### Application:

For drilling concrete, natural stone, and masonry.

#### Note:

When using long drills > 500 mm, first drill a pilot hole at least 150 mm deep with a shorter drill (preferably of the same Ø).

Shank: SDS Max

Flute length: 450 mm

### Technical description

|                                  |                 |
|----------------------------------|-----------------|
| Flute length                     | 450 mm          |
| Ø                                | 28 mm           |
| overall length                   | 570 mm          |
| Number of cutting edges Z        | 2               |
| Tool material                    | Carbide         |
| Use with impact / without impact | Impact drilling |
| Shank                            | SDS Max         |

Type of product

Masonry drill