



Kati® Blitz compact fibreglass rod in a plastic box, Band length: 50 m



Order data

Order number	814870 50
GTIN	2050000998102
Item class	86A

Description

Version:

3 mm thick fibreglass rod **accepts pushing force** up to 5 kN yet is **highly flexible** (down to a radius of 55 mm); ideal for pulling cables into complicated runs where conduit is already laid or where there are many bends in the conduit.

Adhesive-bonded ferrule at each end with an M5 thread for optional attachment of spring guide tips, pulling grips or pulling eyes.

Supplied with:

Accessories securely stored in a plastic box: 2 spring guide tips \varnothing 7 and \varnothing 10 mm, 5 pulling eyes, 1 pulling grip for cable \varnothing 6 - 9 mm, 5 starting/end joints, 3 coupling joints, 1 special adhesive 3 g, 1 power disc.

Tensile strength: 1 kN

Technical description

Tensile strength	1 kN
Band length	50 m

Accessories

Start ferrule M5	814740
------------------	--------

Adhesive	814750
Cable slip agent	814760
Sprung spherical head M5 Head Ø 10 mm	814720 10
Push handle Easy Grip	814775
Pulling grip for cable M5 Type 6	814710 6
Sprung spherical head M5 Head Ø 7 mm	814720 7
Pulling grip for cable M5 Type 10	814710 10
Lead bulb M5 with eye	814730