



## All-steel high-performance clamp with special jaw anvil, Jaw capacity: 500 mm



### Order data

|              |               |
|--------------|---------------|
| Order number | 861100 500    |
| GTIN         | 4008158007328 |
| Item class   | 83K           |

### Description

#### Version:

Beam and fixed jaw made of bright steel section (special profile), tempered and electro-galvanised. Slide jaw made of steel, drop-forged, tempered, and electro-galvanised. Wear-resistant smooth-running steel spindle with trapezoidal thread. Long working life due to heat-resistant special pressure pad with sintered steel inlay, can tilt through 35°. Spindle tempered and burnished with adjustable clamp handle.

#### Application:

For heaviest duty clamping of workpieces in steel construction, blacksmith's shops, HGV bodywork, machine tool manufacture etc. The movable special jaw anvil permits clamping diagonal workpieces up to 35°. **Maximum clamping pressure up to approx. 12000 N.**

Cross section of the slide rail: 34×13 mm

Throat: 140 mm

Weight: 3.4 kg

### Technical description

|                                 |          |
|---------------------------------|----------|
| Cross section of the slide rail | 34×13 mm |
|---------------------------------|----------|

|                 |        |
|-----------------|--------|
| Weight          | 3.4 kg |
| Throat          | 140 mm |
| Jaw capacity    | 500 mm |
| Type of product | Clamp  |

---

## Accessories

|  |        |
|--|--------|
| Clamp head including fastenings            | 861130 |
| Spindle with tightening bar and clamp head | 861140 |