



## Ceiling and assembly support, maximum length: 300 cm



### Order data

Order number	861780 300
GTIN	4008158041261
Item class	83K

### Description

#### Version:

Extremely stable structure thanks to high-tensile steel pipe and non-slip PVC contact faces. One-handed operation thanks to 2-component plastic grip with pump mechanism. Pushbutton for quick extension and retraction of the telescopic rod. Holding force adjustable by twisting the support on the grip. When the **telescopic rod is fully retracted a maximum load of 200 kg can be held**. The contact faces can also be **pivoted steplessly** for use at angles **-45° to 45°**. When used at an angle, load capacity is limited to max. 40 kg.

#### Application:

For fixing plasterboard, wooden boards, panels, roof laths, metal strips, foils and luminaires at a height of up to 3.00 m. Can also be used without problems at angles due to the pivoted and non-slip PVC contact faces.

overall length: 170 - 300 cm

maximum load capacity: 130 kg

Weight: 3.5 kg

### Technical description

Material of handle	2-component plastic
--------------------	---------------------

Special features	can be tilted
Special features	non-slip
maximum load capacity	130 kg
Material	Steel
Pivot angle	-45 - 45 degrees
overall length	170 - 300 cm
suitable for	Metal strips
suitable for	Wooden boards
suitable for	Foils
suitable for	Roof laths
suitable for	Plasterboard
suitable for	Lamp bodies
suitable for	Panels
Carrier plate	9×7 cm
Weight	3.5 kg
Type of product	Ceiling support / assembly support

---

## Accessories

Multi-function/laser holder Type 1	861785 1
------------------------------------	----------