



## Two-leg extractor, Type: 4



### Order data

Order number	880100 4
GTIN	4021176009761
Item class	83U

### Description

#### Version:

With reversible extraction legs (**for external and internal extraction**). Extraction legs adjustable on cross beam for different workpiece  $\varnothing$ . Extraction legs and cross beam of high-quality tool steel; sturdy double-ended spindle (ball end and point end).

#### Application:

Universally applicable for extracting bearings, discs, gear wheels etc. On model 880100 size 5 the depth of reach can be extended from 400 mm (normal) up to 700 mm by adjusting the legs.

External clamping range: 520 mm

Internal capacity: 200 - 590 mm

Depth of reach up to: 200 mm

### Technical description

Internal capacity	200 - 590 mm
External clamping range	520 mm
Depth of reach up to	200 mm

## Accessories

Pair of extended extractor legs Type / Clamping depth 4/500 mm	880300 4/500
Spare extractor legs (3 pieces) Type / Clamping depth 3/200 mm	880220 3/200
Pair of spare extractor legs Type / Clamping depth 3/200 mm	880200 3/200
Spare pressure spindle Type 4	880150 4
Pair of extended extractor legs Type / Clamping depth 3/300 mm	880300 3/300
Hydraulic pressure spindle Type 1	880170 1